


Rubber Flooring Performance Properties

DECORATIVE SLATE, DECORATIVE HAMMERED, CLASSIC RAISED ROUND/SQUARE		
Gauge	0.125"	3.17 mm
Sizes	35 ¹¹ / ₁₆ " x 35 ¹¹ / ₁₆ "	905 mm x 905 mm
	17 ¹³ / ₁₆ " x 17 ¹³ / ₁₆ " Micro-Squared™	452 mm x 452 mm Micro-Squared™
Profiles & Colors	Decorative Slate	10
	Decorative Hammered	10
	Classic Raised Round	16
	Classic Raised Square	9
ASTM F-1344 - Std Specification for Rubber Floor Tile	Exceeds Requirements	
ASTM E-648 / NFPA 253 - Fire Resistance	Class 1	
Critical Radiant Flux CRF (W/cm ²)	<1.10	
ASTM E-662 - Smoke Density	Class 1 ≤450	
ASTM E-84 - Fire Resistance (Steiner Tunnel)	Class 2	
ASTM D-3389 - Abrasion Resistance	Exceeds Requirements	
ASTM D-2240 - Hardness	≥ 85 Shore A	
ASTM D-2047 - Static Coefficient of Friction	Exceeds ADA Guidelines	
ASTM F-970 - Static Load	Complies/Exceeds	
ASTM D-297 - Density	1.72 gr/cc	
ASTM D-412 - Tensile	1,000 psi	
ASTM D-412 - Elongation	170%	
ASTM D-624 - Tear Die	190 lb/in	
ASTM F-925 - Chemical Resistance	Complies (See page 22)	
ASTM F-1515 - Light Aging	Complies	
ASTM F-1514 - Heat Resistance	Complies	
Limited Wear Warranty	10 Years	



SPORTS FLOORING		
Gauge	0.125" and 0.236"	3.17 mm and 6.0 mm
Sizes	35" x 35"	890 mm x 890 mm
Profiles & Colors	6	Slate
Resistance To Golf Spikes, Cleats & Skate Blades	Excellent	
ASTM D-2240 - Hardness Shore A	80 ± 5	
Cigarette Burn Resistance	Excellent	
Limited Wear Warranty	5 Years	



DECORATIVE ROLLED RUBBER		
Gauge	0.080"	2.0 mm
Sizes	50" x 50"	1270 mm x 15.24 m
Profiles & Colors	6	Decorative Patterns
Limited Wear Warranty	Five Years	

SPECIALTY PROFILES

Square		Deck Point	
35 ¹¹ / ₁₆ " x 35 ¹¹ / ₁₆ " (905 mm x 905 mm) Pattern height = 0.635 mm Overall Thickness = 3.17 mm		35 ¹¹ / ₁₆ " x 35 ¹¹ / ₁₆ " (905 mm x 905 mm) Pattern height = 1.03 mm Overall Thickness = 3.17 mm	
Tactile		<i>Special order items: ask your sales consultant for complete details.</i>	
35 ¹¹ / ₁₆ " x 35 ¹¹ / ₁₆ " (905 mm x 905 mm) Pattern height = 0.833 mm Overall Thickness = 3.17 mm			

Rubber Flooring Specifications

GENERAL	
All VPI Rubber Flooring; Decorative Slate, Decorative Hammered, Classic Raised Round and Square shown on the finish schedule, or otherwise listed here within, shall be furnished by VPI, LLC, 3123 South 9th Street, Sheboygan, WI 53082-0451. All VPI Rubber Flooring shall comply with ASTM F-1344 and meet Class 1 Fire Rating Standards as tested to ASTM E-648/ASTM E-662 and ASTM E-84, Class 2. All VPI Rubber Flooring shall be (specify: Decorative Slate, Decorative Hammered, Classic Raised Round and Square) profiles in 17 ¹³ / ₁₆ " x 17 ¹³ / ₁₆ " (452 mm x 452 mm) Micro-Squared™ or 35 ¹¹ / ₁₆ " x 35 ¹¹ / ₁₆ " (905 mm x 905 mm) sizes and 0.125" (3.17 mm) thickness in the color(s) specified.	
All VPI Harsh Environment Flooring shown on the finish schedule, or otherwise listed here within, shall be furnished by VPI, LLC, 3123 South 9th Street, Sheboygan, WI 53082-0451. All VPI Harsh Environment Flooring shall comply with ASTM F-1344 and meet Class 1 Fire Rating Standards as tested to ASTM E-84, ASTM E-648/ASTM E-662. All VPI Harsh Environment Flooring shall be (specify: Round) profile in 17 ¹³ / ₁₆ " x 17 ¹³ / ₁₆ " (454 mm x 454 mm) or 35 ¹¹ / ₁₆ " x 35 ¹¹ / ₁₆ " (910 mm x 910 mm) sizes and 0.125" (3.17 mm) thickness in the color(s) specified.	
All VPI Decorative Rolled Rubber Flooring shown on the finish schedule, or otherwise listed here within, shall be furnished by VPI, LLC, 3123 South 9th Street, Sheboygan, WI 53082-0451. All VPI Decorated Rolled Rubber Flooring shall comply with ASTM F-1859 and meet Class 1 Fire Rating Standards as tested to ASTM E-648/ASTM E-662 and ASTM E-84 Class 2. All VPI Decorative Rolled Rubber Flooring shall be 50" x 50" (1,270 mm x 15.24 m) size and 0.080 (2.00 mm) thickness in the color(s) specified.	
All VPI Sports Flooring shown on the finish schedule, or otherwise listed here within, shall be furnished by VPI, LLC, 3123 South 9th Street, Sheboygan, WI 53082-0451. All VPI Sports Flooring shall comply with ASTM F-1344. All VPI Sports Flooring shall be 35" x 35" (890 mm x 890 mm) and 0.125" (3.17 mm) or 0.236" (6 mm) in the color(s) specified.	
INSTALLATION & MAINTENANCE	
All VPI Rubber Flooring, Decorative Slate, Decorative Hammered, Decorative Rolled Rubber, Harsh Environment Flooring and Sports Flooring must be installed in accordance with manufacturer's specifications, including subfloor preparation and recommended adhesive. Refer to "VPI Rubber Flooring Installation and Maintenance" for complete details. Copies can be obtained by calling 800-874-4240, at www.vpiflooring.com, or by writing: VPI, LLC, 3123 South 9th Street, Sheboygan, WI 53082-0451.	

HARSH ENVIRONMENT		
Gauge	0.125" Stud Height: 0.020"	3.17 mm Stud Height: 0.5 mm
Sizes	35 ¹¹ / ₁₆ " x 35 ¹¹ / ₁₆ "	910 mm x 910 mm
	17 ¹³ / ₁₆ " x 17 ¹³ / ₁₆ " Micro-Squared™	454 mm x 454 mm Micro-Squared™
Profiles & Colors	Round Low Profile With Chamfered Edges - 6	
ASTM D-471 - Oil & Grease Resistance	ASTM Oil #1: Excellent ASTM Oil #3: Excellent	
ASTM F-925 - Resistance to Chemicals	Excellent (Acids, Alkalis, Solvents)	
ASTM D-2240 - Hardness Shore A	≥85	
ASTM E-648 - Critical Radiant Flux	≥0.45	
ASTM E-84 - Flame Development	Class 1	
ASTM E-662 - Smoke Density	≤450	
ASTM D-3389 - Abrasion Resistance Taber Abrasion (H-22 Wheel @ 1000 Cycles / 1.0 Kg Load)	Exceeds Requirements	
ASTM D-2047 - Static Coefficient of Friction	Exceeds ADA Guidelines	
Cigarette Burn & Solder Resistance	Excellent	
Limited Wear Warranty	10 Years	
VOCs (Volatile Organic Compounds)	Very Low	
Regular Stair Treads Available in 36", 48" and 72" Lengths		

