

SPRAY BUFFING AGENT

DESCRIPTION

VPI ESD Spray Buff has been especially designed to quickly and simply enhance the long term visual appearance of VPI ESD tile after installation.

To achieve a deep rich luster and make any VPI ESD tile "look like new", simply clean the floor using VPI ESD Ongoing Cleaner and then apply VPI ESD Spray Buff.

USES / BENEFITS

- Extremely economical to use
- High activity
- Cleans & polishes
- Simple to use
- Conductive
- High Luster

SPECIFICATIONS

Color	Water White
Fragrance	Mild
pH	11.0
Coverage	.4,000 sq ft per qt

DIRECTIONS FOR USE

Sweep or dust mop the floor to remove any large debris. Never use oil base treated dust mops. Damp mop or auto scrub using VPI ESD Ongoing Cleaner.

Once the floor surface is clean, dry and free of residue, mist a small area (about a 10'x10' area at a time) with VPI ESD Spray Buff using the trigger on the fine mist setting.

Simply buff floor with a red or natural hair pad, using a slow even sweeping motion until desired appearance is obtained.

NOTE: It is very important to follow the specific directions for cleaning VPI ESD TILE. Treating it otherwise, can negatively impact visual appearance and electrical performance. IMPORTANT: Never buff in excess of 375 RPM.

PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.See container and MSDS for safety.



Everywhere Toll Free: 800-874-4240 www.vpiflooring.com VPI Corporation