



Green Floor Prep & Conditioner

EXTREME PERFORMANCE PREPARATORY AGENT

DESCRIPTION

VPI Green Floor Prep & Conditioner is the first step in the overall VPI Maintenance System. It meets or exceeds nationally accepted green standards for floor care products - based on its reduced levels of volatile organic compounds, biodegradability, and ultra low toxicity. It's a synergistic formulation designed especially for VPI's solid vinyl tile as an optimal preparatory agent when used in conjunction with PRT Flex Shield, PRT Satin Flex Shield, and PRT Cleaner. A must for new tile, it preps and conditions floor removing any trace of manufacturing residue and debris allowing for maximum coating adhesion.

On previously coated flooring, it acts to rapidly liquefy previous treatments and ground in dirt. It requires less time and effort to remove even the most difficult of coatings. Floors are ready to recoat without neutralizing when VPI Green Floor Prep & Conditioner is used as directed. Any prep solution that remains after pick up will evaporate, so no rinsing is required before recoating under normal circumstances.

PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.
See container and MSDS for safety.

USES / BENEFITS

- **Extremely economical to use**
- **Highly Concentrated**
- **Biodegradable**
- **Environmentally Safe**
- **Preps and conditions tile**
- **Meets or exceeds National Green standards for floor care**
- **Can be used by mopping, or in auto scrubbers**
- **Maximizes finish adhesion**
- **Leaves no residue**
- **Removes old finish & sealer**
- **Fantastic on PRT & ESD tile**

SPECIFICATIONS

Color	Water White
Fragrance	Mild
pH conc.	11.0
pH in dilution	10.0
Residue	None
Biodegradable	Yes

DIRECTIONS FOR USE

For NEW PRT TILE, sweep or dust mop the floor to remove any large debris. Never use oil base treated dust mops. Dilute Green Floor Prep & Conditioner (1:10) 13 oz./gal with cool to warm water. Apply liberally to floor. USING A MAROON PAD agitate floor thoroughly with a low-speed rotary machine, or an automatic scrubber. Pick up the solution remains, rinse with clear water only. Allow floor to dry completely before applying PRT Flex Shield, or PRT Satin Flex Shield.

For NEW ESD TILE, sweep or dust mop the floor to remove any large debris. Never use oil base treated dust mops. Dilute Green Floor Prep & Conditioner (1:10) 13 oz./gal with cool to warm water. Apply liberally to floor. USING A RED PAD agitate floor thoroughly with a low-speed rotary machine, or an automatic scrubber. Pick up the solution with a wet vacuum, an automatic scrubber or a mop and bucket. If soil or residue remains, rinse with clear water only. Allow floor to dry. **Optionally**, the floor can then be dry buffed with a RED PAD and brought to a polished finish with a WHITE PAD.

For PREVIOUSLY TREATED solid vinyl tile. Sweep or dust mop the floor to remove any large debris. Never use oil base treated dust mops. Dilute Green Floor Prep & Conditioner (1:5) 25.6 oz./gal with cool to warm water. Apply solution liberally to floor surface. Allow 4 - 5 minutes contact time. Be sure to keep surface wet at all times. USING A MAROON PAD agitate floor with a low-speed rotary machine, or an automatic scrubber. Pick up the solution with a wet vacuum, an automatic scrubber or a mop and bucket. If soil or residue remains, rinse with clear water only. No flood rinsing is necessary if surface appears free of dust and residue. Allow floor to dry completely, then follow the appropriate steps as listed above for either PRT or ESD.

NOTE: It is very important to follow the specific directions for the type of tile you've chosen for your facility - namely PRT or ESD, as it will affect the functionality of the floor.