

Approved LVT , Tile-Plank and Carpet Tile
Platinum High Moisture
Spray Adhesive



**6500
PLATINUM**

PRODUCT CHARACTERISTICS

6500 Platinum is a self-contained spray system that is engineered to adhere luxury vinyl tile and plank to concrete, underlayment grade plywood, metal and fiberglass substrates.

6500 Platinum is warranted to withstand concrete moisture emissions up to 10 lbs./24 hrs./ 1000 ft² or 92% RH and pH up to 12.

ADVANTAGES

- Use 80% less adhesive
- Allows all traffic immediately (including forklifts)
- <0.0 g/ml VOC content
- Non-Toxic, water based adhesive
- No need to shut down HVAC
- Easy water cleanup while adhesive is still wet
- Non-flammable
- High moisture and pH resistance
- No offensive odors

SUITABLE SUBSTRATES

6500 Platinum bonds approved Luxury Vinyl Plank to the following properly prepared smooth, flat, dust free substrates:

- Concrete
- Underlayment grade plywood
- Metal
- Fiberglass

TECHNICAL CHARACTERISTICS

- **6500 Platinum** provides immediate shear strength after installation allowing instant access to finished floor.
- **6500 Platinum** is solvent free, emits no harmful fumes and contains <0.0g/ml VOC's (Volatile Organic Compounds) in content according to EPA test method 24.
- **6500 Platinum** uses non-ozone depleting HFC propellant.
- **6500 Platinum** withstands 10 lbs of vapor emissions, 92% RH and 12 pH.

TECHNICAL DATA

Chemical Type	Water based acrylic blend
Appearance	Milky white frost bubbles
Odor	Sweet mild odor
Flash point	Will not burn
NFPA 704 Flammability Rating	0 (Non-Flammable)
Storage	Do not subject to freezing temperatures.
Shelf life	3 years if unopened.
Open time	4 hours
Dry time	Once adhesive is dry to touch (10-40 minutes)
VOC content	<0.0g/ml calculated
Foot traffic allowance	Immediate
Heavy machinery allowance	Immediate
Resistance to moisture	10 lbs / 1000 sq. ft or 92% RH / 12pH
Underfloor heating systems	Yes



THE UPSIDE-DOWN AEROSOL WITH LEVER

Slide lever prongs underneath valve collar, point tip towards substrate. Press lever to spray adhesive. This is perfect for all sized jobs. Cutting in is simple and most importantly it keeps the installer standing upright.

COVERAGE GUIDE

	UPSIDE DOWN AEROSOL
COVERAGE	100-125 sq. ft.